

**Description**

Semi-synthetic, two-stroke oil with special low-smoke additives to guarantee cleaner combustion and minimal carbon deposits. Suitable for air and radiator-cooled two-stroke engines in intensive use at high r.p.m. Self-mixing.

**Application**

-

**Instructions for use**

Recommended mix ratio is 2%: use 50 ml oil to 2.5 litres of petrol and 2 x 50 ml oil to 5 litres of petrol.

**Performance level**

API TC

JASO FD

ISO-L-EGD

Global GD

Husqvarna 272

2-Stroke DFI

**Typical standard analyses**

Density at 15 °C, kg/l	0,864
Viscosity 40 °C, mm <sup>2</sup> /s	64,60
Viscosity 100 °C, mm <sup>2</sup> /s	9,50
Viscosity Index	129
Flash Point COC, °C	116
Pour Point, °C	-25
Total Base Number, mgKOH/g	1,4
Sulphate Ash, %	0,14

KEES VAN DER SPEK  
TUINMACHINES \* STOLWIJK

Date printed: 10-6-2016

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.